



Chiltern Connections Ltd

Shin-Etsu Honda Grease

Code : **CCL/G3W0M/30S - 30g syringe**
 : **CCL/G3W0M/W01 - 100g tube**

2 Hithercroft Court
 Hithercroft Ind Est
 Wallingford
 Oxfordshire
 OX10 9BT

Tel 01491 824788
 Fax 01491 824799

Email: sales@chilternconnections.co.uk
 Website: www.chilternconnections.co.uk

Chiltern Connections Ltd
 supply products and services throughout
 the electronics production industry

Description of Product

Honda Part number 08798-9013—Shin-Etsu part number G30-M

It is recommended in Honda manuals that you apply silicone grease to the rubber seals of your car every 3-6 months to protect against squeaks and leaks

This item is supplied in two forms - a 30g syringe and a 100g tube.

When applying silicone grease it is recommended that all old grime and grease is removed from the seal before the application of fresh grease. Then put some Shin-Etsu G30-M onto a clean cloth and rub it into the rubber seals around the doors, window and sunroof, the boot and under the bonnet may also require attention. The application process should be repeated twice, to ensure that the grease has been worked into the rubber surface as much as possible.

Item	G30-M
Appearance	Greyish white grease
Specific gravity 25°C	1
Penetration 25°C/JIS worked	240 - 280
Drop point (°C)	Over 200
Oil separation (%) 150°C/100h	2.3
Oxidative stability (MPa) 150°C/50h	0.03
JIS K2220	
Moisture resistance (%)	1
Work stability 100,000 times	400 (max.)
Low-temperature torque value (N · m×10 ⁻⁴) - 60°C (starting/running)	2710/950
MIL-L15719A	
Low-temperature torque value 2,000 N · m×10 ⁻⁴ - 60°C	1 sec
BTB	Free acid or free alkali
Free acid or free alkali	Neutral
Usage temperature range (°C)	- 60 to + 180
Volatile content (%) 150°C/100h	0.41
Low-molecular-weight silicone content (ppm) ΣD3 - D10	Less than 100
